



Color Copy coated silk has a coating specially adapted to digital colour laser printing which gives the paper an elegant satin quality. These features are not only pleasing to the eye but also pleasant to the touch and enhance the overall impression of annual reports, brochures and flyers.



Technical Data: COLOR COPY COATED SILK

| | | | | | |
|---------------------------|----|------------------|-------------|------------|--------------------|
| Basis weight | | g/m ² | ISO 536 | | 135 ± 3.0 |
| Caliper | | µm | ISO 534 | | 112 ± 4 |
| Stiffness 15°/10mm | MD | mN | ISO 2493-1 | | 180 ± 20 |
| Stiffness 15°/10mm | CD | mN | ISO 2493-1 | | 100 ± 10 |
| Smoothness Bekk | | sec | ISO 5627 | | 600 ± 200 |
| Opacity | | % | ISO 2471 | min | 94.0 |
| Moisture abs. | | % | ISO 287 | | 4.8 ± .6 |
| Brightness UV | | % | ISO 2470 | | 103.0 ± 2.0 |
| CIE Whiteness | | % | ISO 11475 | | 139 ± 2.5 |
| Gloss 75° | TS | % | TAPPI T 480 | | 52 ± 4 |

Product meets EN 12281, requirements for copy paper for dry toner imaging processes and ISO 9706, requirements for permanence for paper. Production processes certified according to ISO 9001. Standard measurement uncertainty between laboratories is not incorporated.

SIGNIFICANCE OF VALUES: 2 SIGMA

This specification is valid for one year after issue.